

KEW 2432 - Leakage Clampmeter

KEW 2432 - Leakage Clampmeter

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- **High Sensitive Model**
- **Frequency Selector Switch to eliminate the effect of harmonics.**
- **Three AC current ranges:4mA/40mA/100A.**
- **Resolution 0.001mA.**

Specification:

AC A (50/60Hz)	4/40mA/100A ±1%rdg±5dgt (4/40mA) ±1%rdg±5dgt (0 - 80A) ±5%rdg (80.1 - 100A)
AC A (WIDE)	4/40mA/100A ±1%rdg±5dgt [50/60Hz], ±2.5%rdg±10dgt [20Hz - 1kHz] (4/40mA) ±1%rdg±5dgt [50/60Hz], ±2.5%rdg±10dgt [40Hz - 1kHz] (0 - 80A) ±5%rdg [50/60Hz], ±10%rdg [40Hz - 1kHz] (80.1 - 100A)
Maximum circuit voltage	600V AC/DC (between line/neutral) 300V AC/DC (against earth)
Conductor size	Ø40mm max.
Frequency response	20Hz - 1kHz (40Hz - 1kHz:100A)
Effect of External Stray Magnetic Field	2mA AC approx. in proximity to a 15mm-dia conductor carrying 100A AC
Safety Standard	IEC 61010-1 CAT III 300V Pollution Degree 2 IEC 61010-2-032
Response Time	Approx. 2 seconds
Power source	Two R03 or equivalent (DC1.5V) batteries
Dimensions	185(L) × 81(W) × 32(D)mm
Weight	290g approx.
Included Accessories	9097 (Carrying Case) R03 (1.5V) × 2 Instruction Manual