

## KEW 2432 - Leakage Clampmeter

KEW 2434 - Leakage Clampmeter

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- Least affected by external stray magnetic field.
- 20mA AC max. in proximity to a 15mm-dia conductor carrying 100A AC
- Frequency Selector Switch to eliminate the effect of harmonics.
- Resolution 0.1mA.

AC A (50/60Hz)	400mA/4/100A $\pm 2\%$ rdg $\pm 4$ dgt
AC A (WIDE)	400mA/4/100A $\pm 2\%$ rdg $\pm 4$ dgt [50/60Hz] $\pm 3\%$ rdg $\pm 5$ dgt [40 - 400Hz]
Conductor size	$\varnothing 28$ mm max.
Frequency response	40 - 400Hz
Effect of external stray magnetic field $\varnothing 15$ mm 100A	20mA AC max.
Safety Standard	IEC 61010-1 CAT III 300V IEC 61010-2-032
Power source	R03 (AAA) (1.5V) $\times 2$
Dimensions	169(L) $\times$ 75(W) $\times$ 40(D)mm
Weight	220g approx.
Included Accessories	9097 Carrying Case R03 $\times 2$ Instruction Manual