

KEW 2413R - True RMS Leakage Clampmeter

KEW 2413R - True RMS Leakage Clampmeter

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description

- Large transformer jaws of 68mm diameter makes it possible to clamp on all three or four wires (3 phases) together for leakage current measurement.
- True RMS enables an accurate measurement for distorted waveforms.
- Measurement from mA up to AC 1000A
- Frequency filter switch to eliminate the effect of the harmonics.
- 2 way analogue output terminal
- Resolution 0.1mA

Specification:

AC A (50/60Hz)	200mA/2/20/200/1000A ±2.5%rdg±5dgt (200mA/2/20A) ±3.0%rdg±5dgt (200A, 0 - 500A) ±5.5%rdg (501 - 1000A)
AC A (WIDE)	200mA/2/20/200/1000A ±1.8%rdg±5dgt (50/60Hz) (200mA/2/20A) ±2.0%rdg±5dgt (50/60Hz) (200A, 0 - 500A) ±5.0%rdg (50/60Hz) (501 - 1000A)
Crest factor	3.0 or less
Conductor size	Ø68mm max.
Frequency response	40Hz - 1kHz
Output	Waveform : AC200mV against the maximum value of each range (1000A range is 100mV) Recorder : DC200mV against the maximum value of each range (1000A range is 100mV)
Applicable standards	IEC 61010-1 CAT III 300V Pollution degree 2 IEC 61010-2-032
Power source	6F22 (9V) × 1 *Continuous measuring time: Approx. 60 hours
Dimensions	250(L) × 130(W) × 50(D)mm
Weight	Approx. 570g (including battery)
Included Accessories	9094 (Carrying Case) 6F22 × 1 Instruction Manual
Optional Accessories	7073 (2WAY Output Cord)