

KEW 2510 - DC Miliamp Clamp Meter

DC Miliamp Clamp Meter (Bluetooth function) 20/120mA

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [KYORITSU](#)

Description



- Measures 4 to 20 mA instrumentation and process signals without breaking the loop
- Memory function stores up to 192000 data useful for monitoring the signals over time and fault finding
- Transfer data to PC via Bluetooth
- Top class measurement 0.2% accuracy
- 6mm clamp jaw easy to use in tight places
- LED light for illuminating the measurement spot
- Analog output terminal to allow the connection to a recorder or a digital multimeter

Specification

AC A	20/100mA(Auto ranging) ±0.2%rdg±5dgt (0.00mA - 21.49mA) ±1.0%rdg±5dgt (21.0mA - 120.0mA)
Conductor size	6mm max.
Analog output	Recorder: DC1000mV against DC100mA

Clampmeter: KEW 2510 - DC Milliamp Clamp Meter

Applicable standards	IEC 61010-1, Pollution degree 2 IEC 61010-2-032, IEC 61326-1(EMC) IEC 60529 IP40, EN50581(RoHS)
Operating temperature & humidity range	-10 - +50? <85%
Storage temperature & humidity range	-20 - +60? <85%
Power source	R6/LR6(AA) (1.5V) x4 (Alkaline LR6 is recommended.) External supply (AC adapter MODEL8320)
Communication interface	Bluetooth Ver2.1+EDR Class2
Dimensions / Weight	111(L)x61(W)x46(D)mm : Display unit 104(L)x33(W)x20(D)mm : Sensor 700mm : Sensor Cable Approx. 310g(including batteries)
Included Accessories	8320(AC adapter), KEW Windows for 2510(Software) 9096(Carrying case), LR6(AA)x4, Instruction manual Software installation manual
Optional Accessories	7256(Output cord)